


EXTERIOR DOOR SYSTEMS | INTERIOR DOOR SYSTEMS | **COMMERCIAL** | HARDWARE



COMMERCIAL
2022



madero.ca

Madero has been a distributor to building supply dealers in Western Canada since 1987. We have a complete commercial offering to support the retail packaged products available.

Contact your sales associate to determine the best products for your commercial project.



XL Retail Display



Large Retail Display

Madero's Commercial Retail Stocked Display

Madero offers a full line of architectural hardware, commercial hollow metal doors and frames, building accessories and specialty products. With access to a wide variety of products from industry-leading manufacturers, Madero is able to source the necessary materials for your customer's building project.

STEP 1. CHOOSE YOUR FRAME

EXPANDABLE JAMB KIT

Daybar Expandable Series Frames are an ideal solution for commercial building applications and retrofit work on existing buildings, specifically when existing wall types are unknown or vary throughout the project.



EF-K SQUARE CORNER, 18 GA.

Height: 6/8 to accept 79-1/8" door slab, 7/0 to accept 83-1/8" door slab

Width of Door Slab:

Nominal: 2/8 or 3/0

Actual: 31-3/4 or 35-3/4

Expandable from 4-1/2" to 7-7/8"

Swing: Reversible 6/8, Handed LH or RH 7/0

Kit Includes:

Jamb Set

- 18 ga. Galvanneal steel
- 3 pieces: header, hinge jamb and single strike jamb for assembly in wall openings during construction or renovation

Hinges (3 included)

- 4-1/2"x4" ball bearing commercial grade hinges
- Square corners
- Non-removable pin
- Satin Chrome 26D finish

Expandable Slide Bracket

- 16 ga. Galvanneal steel, spot welded to frame
- 3 sliders on frame jambs and two sliders on frame heads allow for smooth operation


Reinforcements

- Welded to the frame for 3 hinges and strike placement
- Strike jamb leg is prepped for 4-7/8" ANSI strike
- Closer reinforcement is 12 ga. and welded to the header

The frame has a interlocking header that attaches to the jamb legs and is fixed into place with drywall screws when the frame is installed against both sides of the wall.

The frame has two frame face dimple locations on the jamb legs and one in the centre of the header, as well as two holes to attach the header to the frame.

There are no anchors required for the EFK frame. The bottom dimple holes on each side screw to the drywall frame to ensure its stability.



Intertek

Fire rated from 45 up to 90 minutes

PRIMER NOT REQUIRED

Galvanneal steel is matte grey and ready for the finish paint



4-1/2"x4" NRP ball bearing hinges

OPTIONAL JAMB SPECIFICATIONS

- Deadbolt prep - contact sales associate for details
- Drywall frames and welded frames

STANDARD SERIES

Expandable from 4-1/2" to 7-7/8"

FIRE RATING

20 to 90 minute



Intertek

Nominal Door Size	Actual Door Size	Rough Opening	Swing
2/8 x 6/8	31-3/4" x 79-1/8"	33-3/4" x 81"	Reversible
3/0 x 6/8	35-3/4" x 79-1/8"	37-3/4" x 81"	Reversible
2/8 x 7/0	31-3/4" x 83-1/8"	33-3/4" x 85"	Handed
3/0 x 7/0	35-3/4" x 83-1/8"	37-3/4" x 85"	Handed

STEP 2. CHOOSE YOUR DOOR

HOLLOW METAL DOORS

The Madero retail door program includes 20 gauge hollow metal doors for commercial buildings, outbuildings and fire rated residential applications. LS series Galvanneal steel doors are available with two core options; honeycomb core for interior use, or insulated with polystyrene or polyurethane for exterior applications and sound transmission control.

20 GA. LOCKSEAM STEEL DOOR 1-3/4"

Lock seam and beveled edges mechanically interlocking seams on door edges only.

Closer Reinforcement: 14 ga. closer reinforcement, fitted to 16 ga. inverted top channel

Hinge Reinforcement: 7 ga. hinge reinforcement; to accept (3) 4-1/2" hinges

Lock Preparation: ANSI 161 lock reinforcement; 14 ga. prepared for 2-3/4" backset

Beveled to 1/8" or 2 degree bevel

Size Specifications: 6/8 reversible doors will accommodate inswing, outswing, left hand or right hand. 7/0 doors require handing and accommodate inswing or outswing.


NOTE: Special order available in 2/0 to 3/6 widths.

Nominal size	Actual size
2/8 x 6/8	31-3/4" x 79-1/8"
3/0 x 6/8	35-3/4" x 79-1/8"
2/8 x 7/0	31-3/4" x 83-1/8"
3/0 x 7/0	35-3/4" x 83-1/8"

Core Options:


Honeycomb core (HM)

- **Usages:** Interior, fire rated
- **Specs:** R Value 2.5, STC 32




Polystyrene (HMIS)

- **Usages:** Exterior, sound
- **Specs:** R Value 6.6, STC 34




Hinge Placement:

6/8 Template



7/0 Template



DAYBAR




Honeycomb filled doors are fire rated to 90 minutes with a label attached.

PRIMER NOT REQUIRED

Galvanneal steel is matte grey and ready for the finish paint

WHI listed door glazing kits available. Contact your sales associate.



WHAT IS DAYBAR QUALITY?

Daybar quality is built on 50 years of manufacturing experience, broad fire and physical endurance certification capabilities and the best warranty program available in the industry.

STEP 3. CHOOSE YOUR HARDWARE

HINGES

Note: Hinges are included in the expandable jamb frame kit.

NRP BALL BEARING 4-1/2" HINGES (OUTSWING) BALL BEARING 4-1/2" HINGES (INSWING)

Specifications:

- 4-1/2" X 4" Ball Bearing Hinges / Set of 3
- Non removable pin (NRP) for outswing application
- Suitable for moderate to high traffic applications
- Satin Chrome finish
- Quality wood screws and undercut machine screws are included

SELF CLOSING HINGE 4-1/2" X 4 SQ

Specifications:

- 4-1/2" X 4" self closing hinge
- Suitable for moderate to high traffic applications
- Satin Chrome finish
- Quality wood screws and machine screws are included



Non-removable pin ball bearing 4 1/2" hinges



Self Closing 4 1/2" hinges

DOOR CLOSERS

Safety, security and uncompromising value.

SC90 SERIES DOOR CLOSER

Designed for light to moderate duty and for interior/exterior applications, the Falcon Series closers ensure smooth and reliable operation while meeting ADA accessibility requirements. The SC90 series is preset for easy installation.

Specifications:

- Grade 3, single piece cast aluminum body
- Closer mounts hinge side, top jamb or parallel arm
- UL rated
- Non handed for left or right hand swinging doors
- Separate adjustable general speed or latch speed
- 10 year warranty
- SC93 supports door weight of 90-145 lbs
- SC94 supports door weight of 125-190 lbs

SC61 SERIES DOOR CLOSER

Intended for interior use with aluminum storefronts and mixed-use complexes.

Specifications:

- Single piece cast aluminum body
- Non handed for left or right hand swinging doors
- Separate adjustable general speed or latch speed
- 10 year warranty
- Certified Commercial Grade 1
- 689 Aluminum Finish

FALCON® *A division of Allegion Hardware.*



SC93 Door Closer



SC94 Door Closer



SC61 Door Closer

STEP 3. CHOOSE YOUR HARDWARE

KNOBS, LEVERS & DEADBOLTS

FALCON

A division of
Allegion Hardware.

24IP6F SINGLE CYLINDER DEADBOLT

Specifications:

- Integrated anti-pry shield behind cylinder assembly for added security and quicker installation
- Integrated trim design - fewer pieces out of box and improved installation time
- Tapered front resists wrenching
- Accepts small format interchangeable style cores (SFIC) and conventional cylinders
- Adjustable backset with lock-in-place design for greater versatility
- Heavy duty saw-resistant bolt with spinning hardened steel pin inside for additional protection
- ADA compliant thumbturn Grade 2



Single Cylinder Deadbolt

DANE SERIES LEVERS

Specifications:

- Passage, Privacy, Keyed Entrance
- Grade 2 Ansi tested
- Locks are UL listed 3 hour A Label
- Locksets adjust to fit 1-3/8" to 1 3/4" door thickness
- All locksets are non-handed
- Heavy duty springs on trim for lever return and sag prevention
- Trim is thru-bolted
- All levers are solid and meet the necessary disability requirements



Dane Lever

HANA SERIES KNOBS

Specifications:

- Passage, Privacy, Keyed Entrance
- Grade 2 Ansi tested
- Locks are UL listed 3 hour A Label
- Locksets adjust to fit 1-3/8" to 1-3/4" door thickness
- All locksets are non-handed
- Heavy duty springs on trim for knob return and sag prevention
- Trim is thru-bolted



Hana Knob

STEP 3. CHOOSE YOUR HARDWARE

HEAVY DUTY CHECK CHAIN

Only required for exterior applications where wind will be a factor. It is added to support the closer and eliminate stress on the hinges

Specifications:

- 33" chain has the length to allow full 90 degree opening of the door
- Vinyl covering will not crack like plastic
- Cast aluminum mounting brackets



Checkchain with vinyl cover and cast aluminum mount

DOOR STOPS

SI22 WALL MOUNT DOOR STOP

Specifications:

- 2-1/2" concave wall stop, 1" projection
- Suitable for moderate to high traffic applications
- Satin Chrome finish
- Mounting hardware included



SI22 Wall Mount Door Stop

T218 FLOOR MOUNT DOOR STOP

Specifications:

- 1/2" height base adjustable, high style
- Suitable for moderate to high traffic applications
- Satin Chrome finish
- Mounting hardware included



T218 Floor Mount Door Stop



STEP 4. GRAB A WEATHERSTRIP KIT

SILL & WEATHERSTRIP KIT

SILL AND WEATHERSTRIP KIT

Designed for exterior use single entry frames requiring high performance weatherstripping, sill and sweep.

Kit Includes:

Sill


- Extruded aluminum
- 5" wide x 1/2" rise x 36" long
- Punched and countersunk for #10 Robertson flat head wood screw
- Wheelchair accessible
- UL Fire Labelled

Weatherstrip

- 1 set 1-36" & 2-84"
- Extruded aluminum c/w cold temperature vinyl insert.
- Actual size: 1-1/8" (28.7mm) wide.

Sweep

- 1 pc. 36" brush sweep
- Extruded aluminum clear anodized
- Actual size: 1-3/8" (28.7mm) high x 36" length.



Sill



Weatherstrip



Sweep





WELDED STEEL FRAMES

Quick Ship! All Madero Distribution Centres stock these products for immediate delivery.

STANDARD WELDED FRAME



Frame Specifications:

- 5-3/4" jamb depth; 3/0 x 7/0 and 3/0 x 6/8; left hand and right hand
- Existing wall anchors (can be used with pre-existing wood, steel stud or masonry walls)
- Both Regular arm and Parallel arm closer reinforcements
- 45 min manufacturer embossed FRR label

Rough Opening Size Requirements:


- 3/0 x 6/8 = 40-1/4" x 82-1/8"
- 3/0 x 7/0 = 40-1/4" x 86-1/8"

SINGLE DRILLED PART NUMBERS

Q-AS5 3/4 3/0X6/8 LH	Q-AS5 3/4 3/0X7/0 LH
Q-AS5 3/4 3/0X6/8 RH	Q-AS5 3/4 3/0X7/0 RH

DEADLOCK STRIKE PART NUMBERS

Q-AS5 3/4 3/0X6/8 DL	Q-AS5 3/4 3/0X7/0 DL
Q-AS5 3/4 3/0X6/8 DR	Q-AS5 3/4 3/0X7/0 DR



Preps



Single Prep



Double Prep



Closer
Reinforcement



Embossed Label



DOUBLE DRILLED AND GLAZED HOLLOW METAL DOORS

Quick Ship! All Madero Distribution Centres stock these products for immediate delivery.

DOUBLE DRILLED AND GLAZED COMMERCIAL STEEL DOORS

Door Specifications:

- 3/0 x 7/0 and 3/0 x 6/8; left hand and right hand
- Designed for interior or exterior use in any commercial setting
- Polystyrene core (R7 Insulation Value)
- 20 gauge (HMIS20) or 18 gauge (HMIS)
- Machine prepped for 3 commercial hinges, and double drilled for lockset and deadbolt

GLAZED STEEL DOORS

Door Specifications:


- Half lite glazing: 24" x 36" for 7/0 Doors, 24" x 32" for 6/8 Doors
- Sealed unit, dual pane, clear tempered glass

Nominal Size vs Actual Size:

- 3/0 x 6/8 = 35-3/4" x 79-1/8"
- 3/0 x 7/0 = 35-3/4" x 83-1/8"

PART NUMBERS

Q-HMIS 3/0X6/8DL HL	HMIS20 3/0X6/8L DD
Q-HMIS 3/0X6/8DR HL	HMIS20 3/0X6/8R DD
Q-HMIS 3/0X7/0DL HL	HMIS20 3/0X7/0L DD
Q-HMIS 3/0X7/0DR HL	HMIS20 3/0X7/0R DD





ALUMINUM ENTRANCE PROGRAM


ALUMINUM ENTRANCE

Door Features:

- Door comes pre-glazed with sealed unit, clear tempered glass
- Door is pre-hung in an assembled thermally broken frame with standard hardware
- Options for interior and exterior use
- Durable and virtually maintenance free
- Maximum security hook bolt locks
- 1" diameter push/pulls included
- Mechanically fastened shear blocks and welded corner construction
- Adaptable to virtually all hardware
- Glass stops with bulb gaskets
- 1/4", 3/8", 5/8" and 1" glazing options available
- Adaptable to meet local building codes
- Ready to install
- Limited lifetime warranty



Standard Hardware:



PB - 21 Push Bar

CY-3 Thumb
Turn and
CY-1 Cylinder



BH-1
Butt Hinge




Adams-Rite 1850 MS
Hookbolt Lock and
FB-1 Face Plate



PH-21 Offset
Panic Pull



Specifications:



Series 212 - Narrow Stile

SKUS

Q-ALUM SGL CA NS LHO

Q-ALUM SGL CA NS RHO

BULK COMMERCIAL HARDWARE

Buy in case lot quantities for additional discount!

HINGES

- **NRP Ball Bearing 4-1/2" Hinges (Outswing) / Ball Bearing 4-1/2" Hinges (Inswing)**

Suitable for moderate to high traffic applications.

- **Self Closing Hinges 4-1/2" x 4"**

Self closing hinges suitable for moderate to high traffic areas.



LOCKSETS AND DEADBOLTS

- **Schlage AL series Commercial Locksets**

Designed to offer reliable security in medium to high traffic areas. With a Grade 2 rating, the AL Series suits any interior and exterior application.

- **Falcon W series Commercial Locksets**

A quality product at a great value price point. Ideal for low traffic commercial doorways and meets Grade 2 standard for durability.



EXIT DEVICES AND TRIM

- **Von Duprin 22 Series Exit Devices and Operating Trim**

A quality product solution for medium to low traffic areas where proven reliability is needed.

- **Stanley 300 Series Exit Devices and Operating Trim**

A reliable and durable exit device for light duty commercial applications at a very economical price point.



CLOSERS

- **Falcon SC61 Medium Duty Closers**

Designed for light to medium duty application such as small businesses or office buildings. Comes with a Grade 1 rating as well as UL listing.

- **LCN 4040XP Heavy Duty Closers**

LCN's most durable heavy duty closer, designed for the most demanding high traffic applications. Meets Grade 1 standards and boasts a 30 year limited warranty.





WEATHERSTRIP AND SEALS

- Pemko

Since 1952 Pemko has been a key North American manufacturer of commercial weatherstrip products, carrying full lines of thresholds, fire/smoke seals, door bottoms, perimeter gasketing, sweeps and astragals.

- KN Crowder

A manufacturer with a reputation for quality products, KN Crowder Auto Door bottoms are among the best in the industry.



ACCESSORIES

Madero stocks a wide range of commercial opening accessories, including Flushbolts, Latch Guards, Kick Plates, Overhead Stops, Door Viewers, Push Plates and Door Pulls. We're proud to work with strong value driven vendors such as Ives, Glyn Johnson, Standard Metal, and more in this category of products.



STANDARD METAL
QUALITY BUILDERS HARDWARE



ACCESS DOORS

Cendrex manufactures a full line of Access Doors, Roof hatches and Floor Hatches to meet any job requirement from residential to industrial.

- Flexi-snap Access Panels

A revolution in Access Door design! Made exclusively by Cendrex, these Access Panels are manufactured to the highest standard and are designed to not only look great but significantly reduce labour for installations!



OPERATORS

Ditec HA7 Slim Low Energy Operator

- The slim header blends seamlessly with most standard door frames, and fits into areas where standard operators could not.
- Its quick installation makes it an ideal choice for offices, restrooms and assisted living facilities.



- Ditec HA8 Low Profile Low Energy Operator

- The same power and durability of the standard profile, but with smaller header for applications where clearance is limited.
- High precision gears made for sustained long-term use
- Available as surface applied and can be found in hospitals, retail stores, schools/universities, airports, convention centers, casinos, industrial buildings and offices.



- Ditec HA9 Full Featured Low Energy Operator

- Loaded with features while offering the same quiet, dependable operation you've come to expect in the low-profile header size you love.
- Electro Mechanical design for simple dependable operation
- Perfect for high traffic locations including hospitals, retail stores, schools/universities, airports, convention centers, casinos, industrial buildings and offices.



ENTREMATIC **Ditec**





MADERO COMMERCIAL PROJECTS SERVICES

OUR SERVICES

Madero Commercial Services offers full Estimating and Project Management services for door, hardware and building specialty requirements of all sizes of commercial, multi-family, industrial, and institutional construction projects. We are fully bonded and COR certified.

OUR SERVICES INCLUDE:

- Shop drawings
- Detailing and product labelling

OUR SERVICES DO NOT INCLUDE:

- Site measurements
- Delivery to job site
- Review or involvement of contracts
- Attendance at job site meetings

OUR AREAS OF EXPERTISE

- Hollow Metal Doors and Frames
- Wood Doors
- Aluminum Entrances
- Architectural Hardware
- Access Control Systems
- Automatic Operators
- Access Panels & Roof Hatches
- Washroom Accessories
- Toilet Partitions
- Lockers
- Mailboxes
- Operable Walls
- Specialty Doors (Crash doors, Cooler doors, Folding Doors)

CONTACT INFORMATION

Email: Commercial@westfour.ca

All commercial quote requests can be sent to this email address. Please include as much information as possible, full plans and specs if available.

Phone: 1-800-667-6977 (Press 2 for Commercial Inquiries)



madero.ca

Visit madero.ca to access our e-commerce site to discover all of the available commercial products (doors, frames, hardware and building specialties) that Madero can supply you with for your next commercial project!

BEFORE YOU START

Where is this door going? _____

Traffic Usage: ☐ Low ☐ Medium ☐ High

Is it a Fire Rated Opening? ☐ Yes ☐ No



Madero
Doors & Hardware

ORDERING CHECKLIST

for all of your


COMMERCIAL

Door & Hardware Projects

STEP 1. CHOOSE YOUR FRAME


3 Pc, Knockdown Frames:

18 Gauge



☐ 350 ☐ 462 ☐ 487


16 Gauge




☐ 525 ☐ 675 ☐ 725

Welded Frames - 16 Gauge: (Require Anchors)


Throat Size




Expandable Frames Field Adjustable for Walls:



☐ **XF (REV)**
4-1/2" to 7-7/8"




☐ **EF2**
5-3/8" - 8-11/16"




☐ **EF3**
8-11/16" - 12"

Wall Anchors for Welded Frames:



Masonry
Wire Anchor
(WA)
☐



Steel
Building
Anchors
(SBA)
☐



Existing Wood
Wall Anchor (EWA)
☐

Existing Masonry
Wall Anchor (EMA)
☐



Adjustable Stud
Anchor - Wood
or Steel Studs
(Anchor A)
☐



Masonry
Tube Shim
Anchor
☐

STEP 2. CHOOSE YOUR DOOR

Choose door width:

☐ 2' ☐ 2'4" ☐ 2'6" ☐ 2'8" ☐ 2'10" ☐ 3' ☐ 3'6" ☐ 4'

Choose door height:

☐ 6'8" ☐ 7'


Choose door gauge:

☐ 20 ☐ 18 ☐ 16


Insulated ☐ Yes ☐ No

Double Drilled ☐ Yes ☐ No


Standard Door Types:



Handing of Door:




Right Hand (RH)




☐

Left Hand (LH)




☐

Right Hand Reverse (RHR)



☐

Left Hand Reverse (LHR)



☐

Frame / Door / Hardware Configuration:

☐



Single Drill,
Hinges

☐



Double Drill,
Hinges

☐



Single Drill,
Closer Prep,
Hinges

☐



Exit Device,
Closer, Hinges

☐



Single Drill, Lock,
Closer, Flush Bolt,
Hinges

☐



Exit Device, Closer,
Removable Mullion,
Hinges

STEP 3. CHOOSE YOUR HARDWARE

- | | | | | |
|--|--------------------------------------|--------------------------------------|-------------------------------------|---|
| <input type="checkbox"/> Hinges | <input type="checkbox"/> Privacy Set | <input type="checkbox"/> Exit Device | <input type="checkbox"/> Door Pull | <input type="checkbox"/> Weatherstrip / Sweep / Threshold |
| <input type="checkbox"/> Keyed Lockset | <input type="checkbox"/> Deadbolt | <input type="checkbox"/> Flushbolt | <input type="checkbox"/> Push Plate | <input type="checkbox"/> Door Viewer |
| <input type="checkbox"/> Passage Set | <input type="checkbox"/> Closer | <input type="checkbox"/> Check Chain | <input type="checkbox"/> Kick Plate | <input type="checkbox"/> Door Stop |

Comments _____

Customer Signature: _____ Date: _____

Store Name or #: _____ Tag: _____ PO #: _____


Contact at Store: _____



Looking for a high quality, complete door and hardware package for your home? Madero offers a wide array of door designs and configurations with highly customizable glass and hardware options suitable for both interior and exterior applications.



Entry Series



Garden Patio Doors



Artisan Doors



Multi-Family



Larson Products



Interior Doors

Calgary

T 1.800.667.6977 • F 1.403.204.7665

Saskatoon

T 1.800.667.6977 • F 1.306.934.7644

Winnipeg

T 1.800.667.6977 • F 1.204.594.0201

madero.ca