



## DAKOTA UTILITY

Steel Slab | Composite Frame



## TITAN UTILITY

Fiberglass Slab | Composite Frame

- Reversible for inswing, outswing, left hand or right hand
- Designed for commercial and pole building applications
- Prepped for commercial hardware c/w 4-7/8" ANSI strike installed
- Single drilled (double drilling available as an add-on)

# UTILITY DOOR SYSTEM SPECS



Madero

## DAKOTA UTILITY

### Steel Slab

### Composite Frame

**Door** Flush steel door slab, white polytex finish; polyurethane core and 16" wood lock block



Madero

## TITAN UTILITY

### Fiberglass Slab

### Composite Frame

**Door** Smooth, pre-pigmented white fiberglass door slab with composite stiles and rails, polyurethane core and full length steel reinforced lock block



<b>Sizes</b>	Widths: 2/8, 2/10, 3/0 and 3/6; Height: 6/8
<b>Frame</b>	Available in 4-9/16" or 6-9/16" jamb depths. White maintenance-free composite jamb will not discolour, absorb moisture, splinter or rot. Brown kerf weatherstripping.
<b>Construction</b>	Mechanically fastened with screws, top and bottom
<b>Drilling</b>	Single drill or double drill available. C/W 4-7/8" ANSI strike (2 strikes included with double drill). Door slab prepped for mortise latch, commercial specification.
<b>Sill</b>	Top and bottom solid composite agricultural sill (walnut colour) – low profile, extruded finish, no extensions to snap off and rot proof. H.D. kerf mounted double bubble sweep, mounted top and bottom.
<b>Hinges</b>	4"x4" ball bearing hinges with two NRP hinges included
<b>Warranty</b>	25 year limited manufacturer's warranty on fiberglass door slab; 10 year limited manufacturer's warranty on steel door slab; 5 year limited warranty on components. No painting required to achieve full warranty.



**CALGARY**  
 T 1.866.664.7664  
 F 1.403.204.7665

**SASKATOON**  
 T 1.800.667.6977  
 F 1.306.934.7644

**WINNIPEG**  
 T 1.855.706.0200  
 F 1.204.594.0201