SIMONSWERK

TFCTUS®

TE 541 3D FVZ

for unrebated residential and heavy-duty doors with recessed frame facings

hinge	
-------	--

Technical details

100,0 kg
185,0 mm
28,0/32,0 mm
28,0/33,0 mm
24,0 mm
180° degree

descriptive text

SIMONSWERK TECTUS hinge TE 541 3D for recessed frame facings (FVZ) up to 14,0 mm. Completely concealed for unrebated doors with timber, steel and aluminium frames. With comfortable 3D adjustment, load capacity up to 100 kg, opening angle up to 180°, overall length 185 mm, right hand and left hand applicable, maintenance-free slide bearings, three-dimensionally adjustable: side +/- 3,0 mm, height +/- 3,0 mm, compression +/- 1,0 mm. Finish...



The load capacity mentioned above refers to the use of 2 hinges per door leaf $(1 \times 2 \text{ m})$.

Finger protection on the hinge side due to a small gap between door and frame. Receiver for casing frames on request.

Product features

- completely concealed hinge system
- for timber, steel or aluminium frames
- for unrebated heavy-duty doors
- maintenance-free slide bearings
- with comfortable 3D adjustment (side +/- 3,0 mm, height +/- 3,0 mm, compression +/- 1,0 mm)
- for recessed frame facings (FVZ) up to 14,0 mm


Combination

receiver TE 541 3D EVZ SZ

installation tools

universal milling frame	
template 5 250682 5	frame, step 3
template 5 250942 5	frame / door, step 1
template 5 250943 5	frame / door, step 2
template 5 250944 5	door, step 3





SIMONSWERK TECTUS®


TE 541 3D FVZ

for unrebated residential and heavy-duty doors with recessed frame facings

hinge

Items (DIN reference: DIN right and left hand)

finish(es)	F1-coloured
packing unit	pack of 2
item number	5 400631 0 12402
finish(es)	stainless steel look
packing unit	pack of 2
item number	5 400631 0 12602



recessed frame AUSKOMMENTIERT ENDE